

# Spreader calibrations - KRM

Spreader settings for KAN and KAN Plus range can be found on the Bunn Fertiliser website [www.bunnfertiliser.com](http://www.bunnfertiliser.com).

The spreader settings below are for guidance only. The exact fertiliser rates and spreading patterns using these settings cannot be guaranteed as the application will be affected by the condition of the spreader itself and the environmental conditions at the time of application.

To ensure greater accuracy, the spreader should be recalibrated for application rate and spread pattern using a tray test. Up to date information can be found on the spreader manufacturers website.

Product Name	Spreader (Make/ Model)	Spread Width (m)	Disc/Vane Type	Spreader Height	Tilt (o)	PTO /Disc speed (rpm)	Vane setting / Drop on point / Discharge point	Application Rate (kg/ Ha)	Forward speed (km/h)
KAN 46-0-0	KRM M2	24	E6T	75	+4* Tilt	540	Pos 3+4	200	12
KAN 46-0-0	KRM Bredal	24	Square 4 vane	80		750	D.O.P. 0	200	12
KAN 38N 19S	KRM Ex Trend	24	E6T	75	0* Tilt	540	Pos 1+2	250	10
KAN 38N 19S	KRM Ex Trend	32	E8T	95	+6* Tilt	540	Pos 1+2	250	10
KAN 33N 30S	KRM Ex Trend	24	E6T	75	0* Tilt	540	Pos 1+2	250	10
KAN 33N 30S	KRM Ex Trend	32	E8T	95	+6* Tilt	540	Pos 1+2	250	10

# Spreader calibrations - KRM

Product Name	Spreader (Make/Model)	Spread Width (m)	Disc/Vane Type	Spreader Height	Tilt (o)	PTO /Disc speed (rpm)	Vane setting / Drop on point / Discharge point	Application Rate (kg/ Ha)	Forward speed (km/h)
KAN Plus 31-0-19.5	KRM Ex Trend	24	E6T	75	+4* Tilt	540	Pos 1+2	250	10
KAN Plus 31-0-19.5	KRM Ex Trend	28	E8T	90	+6* Tilt	540	Pos 1+2	250	10
KAN Plus 29-0-17 +9.5S03	KRM Ex Trend	24	E6T	75	+4* Tilt	540	Pos 1+2	250	10
KAN Plus 29-0-17 +9.5S03	KRM Ex Trend	28	E8T	90	+6* Tilt	540	Pos 1+2	250	10
KAN Plus 31-0-0 + 8MgO + 16S03	KRM Ex Trend	24	E6T	75cm from side of disc	+4.0	540	Pos 1&2	200	8
KAN Plus 36-0-8.5 + 8.5S03	KRM Ex Trend	24	E6T	75cm from side of disc	+4.0	540	Pos 3&4	200	8
KAN Plus 36-0-8.5 + 8.5S03	KRM Ex Trend	30	E8T	75cm from side of disc	+6.0	540	Pos 2&3	200	8
KAN Plus 27-14-14	KRM M2	36	E8T	95cm from side of disc	+6.0	600	1&2	200	10
KAN Plus 27-14-14	KRM M2	24	E6T	75cm from side of disc	+2.0	540	1&2	200	10